




Dimension Table

Model	A	B	C	D	E
P11V	6.40	9.80	18.20	9.00	25.80
P12	7.20	11.60	18.30	9.20	29.00
P13	9.00	13.00	23.00	9.60	31.80
P15	10.00	14.90	25.50	10.00	33.30
P17	12.00	17.80	32.00	13.00	40.00



Type	Photos	Model No.	Color	Height	Electrical Ratings & Temperature	UL Listed	Wire Range
Winged		P11V	Yellow	25.80mm 1.016 inch	300 V/600 V Max. 105°C (221°F)	Yes	18-10 AWG, Cu Max. 2 #12 w/1 #14 Min. 3 #18
		P12	Tan	29.00mm 1.142 inch	600 V Max. 105°C (221°F)	Yes	22-8 AWG, Cu Max. 4 #12 Min. 3 #22 Sol
		P13	Red	31.80mm 1.252 inch	300 V/600 V Max. 105°C (221°F)	Yes	18-8 AWG, Cu Max. 5 #12 Sol Min. 3 #16
		P15	Grey	33.30mm 1.311 inch	600 V Max. 105°C (221°F)	Yes	18-8 AWG, Cu Max. 3 #10 Min. 3 #14 w/1 #18
		P17	Blue	40.00mm 1.575 inch	600 V Max. 105°C (221°F)	Yes	14-6 AWG, Cu Max. 3 #8 Sol w/1 #12 Min. 2 #10 w/1 #12